PRODUCT FICHE

gorenje



Ceramic Hob 730602 ECT641BSC USP: Pause function The StopGo function instantaneously turns off all cooking zones while saving all current settings; a simple touch will restore the cooking process. Hence, if the food boils over, the StopGo function can be used to let you clean up and simple continue as soon as you are done. The StopGo function will keep your cooking under control, even when, for any reason, it is interrupted. ChildLock Timer function The countdown timer can be set for up to 99 minutes. If the optimum cooking time for a particular dish is known from experience, the timer can be set and the hob will switch off automatically when completed. A beep will signal that the food is ready. StayWarm The StayWarm function keeps food at a constant temperature of 70°C until the time is right to serve the meal. The food retains its original flavour and temperature until it is served. Residual heat indicator Ensuring even greater safety, residual energy indicators illuminate to reveal which zones of the hob are still radiating heat. As long as an indicator is lit, the respective heating zone should not be touched. It can, however, be used for defrosting or maintaining a dish warm. Type of control

Touch control Product group Hob Another bonus is definitely flush installation, Soft cut hob edges which means smooth transition between the

hob and the worktop. It is easier to clean and brings a modern, stylish look to your kitchen.

Basic information :

Product groupCeramic HobBrandGorenjeProduct name / Commercial codeECT641BSCCommercial code730602Construction typeBuilt-InControl typeBuilt-InControl typeElectronicEnergy inputElectronicTotal number of positions that can be used at the same time4Number of gas burners0Number of electric cooking zones4Number of electric cooking zones0Number of halogen plates0Number of halogen plates0Number of induction plates0Number of control panel4Location of control panelHob frontBasic external material of hob surfaceBackHob degesSignalElectronicSignalElectronic20-240 VGas connection rating0/VGas connection rating0/O AVoltage20-24/0 VFrequency50/60 HzMarks of conformityCE,CAC,UABREZ,GMARKING,JUS00518Length of the product95 mmHeight of the product54 mm	Draduat araun	Ceramic Hob
Product name / Commercial codeECT64/IBSCCommercial code700602CAN code3838782108259Construction typeBuilt-inControl typeElectronicEnergy inputElectronicTotal number of positions that can be used at the same time4Number of gas burners0Number of electric plates0Number of electric coking zones4Number of electric coking zones0Number of electric varming zones0Number of electric outrol plates0Number of electric outrol plates0Number of electric plates0Number of electric outrol plates0Number of solution of control panelBlackHob colorBlackHob colorSolorHob color0Voltage220-240 VGas connection ratingSolorGas connection ratingCE_EAC, UABREZ, GMARKING, JUS00518Length of electric al supply cord0 cmPlug typeWith out plug and supply cord<	Product group	
Commercial code730602EAN code3338782108259Construction typeBuilt-InControl typeElectronicEnergy inputElectronicTotal number of positions that can be used at the same time4Number of gas burners0Number of electric cooking zones4Number of electric plates0Number of halogen plates0Number of electric up plates0Number of electric plates0Number of electric plates0Number of halogen plates0Number of induction plates0Number of electric up plates0Hob doorBlackHob doorBlackHob door0Koord0Current0,0 AVoltage200-240 VFrequency0Marks of conformityCE_EAC,UABREZ,GMARKING,JUS00518Length of electrical supply cord0 cmPlug typeWithout plug and supply condVidith of the p		
EAN code3338782108259Construction typeBuilt-InControl typeElectronicEnergy inputElectronicTotal number of positions that can be used at the same time4Number of gas burners0Number of electric cooking zones4Number of electric cooking zones0Number of radiant plates0Number of radiant plates0Number of electric warming zones4Location of control panelHob frontBasic external materialVithout frameHob dogsBlackHob frame materialWithout frameHob dogs0Gas connection rating6500 WGas connection rating00 WCurrent0,0 AVoltage220-240 VFrequency50/60 HzMarks of conformityCE_EAC,UABREZ,GMARKING,JUS00518Lengt of electricia supply cord0 cmWidth of the product595 mm		
Construction typeBuilt-inConstruction typeElectronicEnergy inputElectronicTotal number of positions that can be used at the same time4Number of gas burners0Number of electric cooking zones4Number of radiant plates0Number of radiant plates0Number of halogen plates0Number of falogen plates0Number of idectric plates0Basic external material of hob surfaceCeramic GlassHob frame materialWithout frameHob dgesN/A Bevelled edgesElectrical connection rating6500 WCarsent in atterial0.0 AVoltage220-240 VFrequency5060 HzMarks of conformityCE,EAC,UABREZ,GMARKING,JUS00518Length of electrical supply cord0 cmVidth of the product595 mm		
Control typeElectronicEnergy inputElectricityTotal number of positions that can be used at the same time4Number of gas burners0Number of electric cooking zones4Number of electric plates0Number of radiant plates0Number of induction plates0Number of electric warming zones4Location of control panelHob frontBasic external material of hob surfaceCeramic GlassHob colorBlackHob degsN/A Bevelled edgesElectricit control panelS00 WGas connection rating6500 WGas connection rating0,0 AVoltage0,0 AYoltage50/60 HzFrequencyS0/60 HzMarks of conformityCE,EAC,LUABREZ,GMARKING,JUS00518Length of electrical supply cord0 crmWith of the product595 mm		
Energy inputElectricityTotal number of positions that can be used at the same time4Number of gas burners0Number of electric cooking zones4Number of electric cooking zones0Number of radiant plates0Number of nalogen plates0Number of induction plates0Number of electric warming zones4Location of control panelHob frontBasic external materialHob frontHob colorBlackHob frame materialWithout frameHob dges0Gas connection rating6500 WGas connection rating0,0 AVoltage20-240 VFrequency0,0 AMarks of conformityCE_EAC,UABREZ,GMARKING,JUS00518Length of electrical supply cord0 cmWithout plate0 cmWithout plate595 mm		
Total number of positions that can be used at the same time4Number of gas burners0Number of electric cooking zones4Number of electric plates0Number of radiant plates0Number of halogen plates0Number of electric warming zones4Location of control panelHob frontBasic external material of hob surfaceCeramic GlassHob colorBlackHob colorN/A Bevelled edgesHob degsN/A Bevelled edgesElectrical connection rating6500 WCurrent0,0 AVoltage220-240 VFrequency50/60 HzMarks of confinityCE_EAC,UABREZ,GMARKING,JUS00518Length of electrical supply cordWithout plug and supply cordWidth of the productS95 mm		
Number of gas burners0Number of electric cooking zones4Number of electric plates0Number of radiant plates0Number of halogen plates0Number of induction plates0Number of electric warming zones4Location of control panelHob frontBasic external material of hob surfaceCeramic GlassHob colorBlackHob degesN/A Bevelled edgesElectrical connection rating6500 WGas connection rating0 WCurrent0,0 AVoltage220-240 VFrequency50/60 HzMarks of conformityCE_EAC,UABREZ,GMARKING,JUS00518Length of electrical supply cordWithout plug and supply cordWidth of the product595 mm		Electricity
Number of electric cooking zones4Number of electric plates0Number of radiant plates0Number of radiant plates0Number of induction plates0Number of electric warming zones4Location of control panelHob frontBasic external material of hob surfaceCeramic GlassHob colorBlackHob degesN/A Bevelled edgesHob degesS00 WElectrical connection rating6500 WGas connection rating0.0 AVoltage200-240 VFrequency50/60 HzMarks of confrontityCE_FAC,UABREZ,GMARKING,JUS00518Length of electrical supply cord0 cmWith of the product595 mm	1	
Number of electric plates0Number of radiant plates0Number of halogen plates0Number of induction plates0Number of electric warming zones4Location of control panelHob frontBasic external material of hob surfaceCeramic GlassHob colorBlackHob frame materialWithout frameHob edgesN/A Bevelled edgesElectrical connection rating6500 WGas connection rating0 WCurrent0,0 AVoltage220-240 VFrequency50/60 HzMarks of conformityCE,EAC,UABREZ,GMARKING,JUS00518Length of electrical supply cord0 cmWidth of the product595 mm	V	0
Number of radiant plates0Number of halogen plates0Number of induction plates0Number of electric warming zones4Location of control panelHob frontBasic external material of hob surfaceCeramic GlassHob colorBlackHob frame materialWithout frameHob edgesN/A Bevelled edgesElectrical connection rating6500 WGas connection rating0 WCurrent0,0 AVoltage20-240 VFrequency50/60 HzMarks of conformityCE,EAC,UABREZ,GMARKING,JUS00518Length of electrical supply cord0 cmPlug typeWithout plug and supply cord	Number of electric cooking zones	4
Number of halogen plates0Number of induction plates0Number of electric warming zones4Location of control panelHob frontBasic external material of hob surfaceCeramic GlassHob colorBlackHob colorBlackHob gesN/A Bevelled edgesElectrical connection rating6500 WGas connection rating0 WCurrent0,0 AVoltage200-240 VFrequency50/60 HzMarks of conformityCE,EAC,UABREZ,GMARKING,JUS00518Length of electrical supply cord0 wPlug typeWithout plug and supply cordWidth of the product595 mm	Number of electric plates	0
Number of induction plates0Number of electric warming zones4Location of control panelHob frontBasic external material of hob surfaceCeramic GlassHob colorBlackHob frame materialWithout frameHob edgesN/A Bevelled edgesElectrical connection rating6500 WGas connection rating0 WCurrent0,0 AVoltage220-240 VFrequency50/60 HzMarks of conformityCE,EAC,UABREZ,GMARKING,JUS00518Length of electrical supply cord0 cmPlug typeWithout plug and supply cordWidth of the product595 mm	Number of radiant plates	0
Number of electric warming zones4Location of control panelHob frontBasic external material of hob surfaceCeramic GlassHob colorBlackHob frame materialWithout frameHob edgesN/A Bevelled edgesElectrical connection rating6500 WGas connection rating0 WCurrent0,0 AVoltage220-240 VFrequency50%0 HzMarks of conformityCE,EAC,UABREZ,GMARKING,JUS00518Length of electrical supply cord0 cmPlug typeWithout plug and supply cordWidth of the product595 mm	Number of halogen plates	0
Location of control panelHob frontBasic external material of hob surfaceCeramic GlassHob colorBlackHob frame materialWithout frameHob edgesN/A Bevelled edgesElectrical connection rating6500 WGas connection rating0 WCurrent0,0 AVoltage220-240 VFrequency50/60 HzMarks of conformityCE,EAC,UABREZ,GMARKING,JUS00518Length of electrical supply cord0 cmPlug typeWithout plug and supply cordWidth of the product595 mm	Number of induction plates	0
Basic external material of hob surfaceCeramic GlassHob colorBlackHob frame materialWithout frameHob edgesN/A Bevelled edgesElectrical connection rating6500 WGas connection rating0 WCurrent0,0 AVoltage220-240 VFrequency50/60 HzMarks of conformityCE,EAC,UABREZ,GMARKING,JUS00518Length of electrical supply cord0 cmPlug typeWithout plug and supply cordWidth of the product595 mm	Number of electric warming zones	4
Hob colorBlackHob frame materialWithout frameHob edgesN/A Bevelled edgesElectrical connection rating6500 WGas connection rating0 WCurrent0,0 AVoltage220-240 VFrequency50/60 HzMarks of conformityCE,EAC,UABREZ,GMARKING,JUS00518Length of electrical supply cord0 cmPlug typeWithout plug and supply cordWidth of the product595 mm	Location of control panel	Hob front
Hob frame materialWithout frameHob frame materialWithout frameHob edgesN/A Bevelled edgesElectrical connection rating6500 WGas connection rating0 WCurrent0,0 AVoltage220-240 VFrequency50/60 HzMarks of conformityCE,EAC,UABREZ,GMARKING,JUS00518Length of electrical supply cord0 cmPlug typeWithout plug and supply cordWidth of the product595 mm	Basic external material of hob surface	Ceramic Glass
Hob edgesN/A Bevelled edgesElectrical connection rating6500 WGas connection rating0 WCurrent0,0 AVoltage220-240 VFrequency50/60 HzMarks of conformityCE,EAC,UABREZ,GMARKING,JUS00518Length of electrical supply cord0 cmPlug typeWithout plug and supply cordWidth of the product595 mm	Hob color	Black
Electrical connection rating6500 WGas connection rating0 WCurrent0,0 AVoltage220-240 VFrequency50/60 HzMarks of conformityCE,EAC,UABREZ,GMARKING,JUS00518Length of electrical supply cord0 cmPlug typeWithout plug and supply cordWidth of the product595 mm	Hob frame material	Without frame
Gas connection rating0 WCurrent0,0 AVoltage220-240 VFrequency50/60 HzMarks of conformityCE,EAC,UABREZ,GMARKING,JUS00518Length of electrical supply cord0 cmPlug typeWithout plug and supply cordWidth of the product595 mm	Hob edges	N/A Bevelled edges
Current0,0 AVoltage220-240 VFrequency50/60 HzMarks of conformityCE,EAC,UABREZ,GMARKING,JUS00518Length of electrical supply cord0 cmPlug typeWithout plug and supply cordWidth of the product595 mm	Electrical connection rating	6500 W
Voltage20-240 VFrequency50/60 HzMarks of conformityCE,EAC,UABREZ,GMARKING,JUS00518Length of electrical supply cord0 cmPlug typeWithout plug and supply cordWidth of the product595 mm	Gas connection rating	0 W
Frequency50/60 HzMarks of conformityCE,EAC,UABREZ,GMARKING,JUS00518Length of electrical supply cord0 cmPlug typeWithout plug and supply cordWidth of the product595 mm	Current	0,0 A
Marks of conformityCE,EAC,UABREZ,GMARKING,JUS00518Length of electrical supply cord0 cmPlug typeWithout plug and supply cordWidth of the product595 mm	Voltage	220-240 V
Length of electrical supply cord 0 cm Plug type Without plug and supply cord Width of the product 595 mm	Frequency	50/60 Hz
Length of electrical supply cord 0 cm Plug type Without plug and supply cord Width of the product 595 mm	Marks of conformity	CE,EAC,UABREZ,GMARKING,JUS00518
Plug type Without plug and supply cord Width of the product 595 mm		
Width of the product 595 mm	•	Without plug and supply cord
	Width of the product	
		54 mm



730602

Depth of the product
Width of the packed product
Height of the packed product
Depth of the packed product
Min height of installation niche
Max height of installation niche
Min width of installation niche
Max width of installation niche
Depth of installation niche
Net weight
Gross weight
Location of control panel

Features :

Short description of the product Automatic programmes Location of 1st heating element Type of 1st heating element Dimension of 1st heating element Power of 1st heating element Location of 2nd heating element Type of 2nd heating element Dimension of 2nd heating element Power of 2nd heating element Location of 3rd heating element Type of 3rd heating element Dimension of 3rd heating element Power of 3rd heating element Location of 4th heating element Type of 4th heating element Dimension of 4th heating element Power of 4th heating element Power on indicator Plate on indicator Type of regulation Type of lid Type of safety device for gas Residual heat indicator Main on/off switch Safety device Accessories included Electronic timer

520 mm 715 mm 145 mm 640 mm 70 mm 0 mm 560 mm 0 mm 490 mm 7,7 kg 8,2 kg N/A BR6AF-T0 - ECT641BSC - ESSENTI No Front left Radiant heater - Hi-light 210 mm 2300/0,0/0,0 W

BR6AF-T0 - ECT641BSC - ESSENTI No Front left Radiant heater - Hi-light 210 mm 2300/0,0/0,0 W **Rear left** Radiant heater - Hi-light 145 mm 1200/0,0/0,0 W Rear right Radiant heater - Hi-light 180 mm 1800/0,0/0,0 W Front right Radiant heater - Hi-light 145 mm 1200/0,0/0,0 W Yes 4 Step energy regulated None 4 Four parts No Yes Switch-off

